

AMV6 WALL-MOUNTED TYPE

- Filter can be cleaned. The filter is removable and can be cleaned for easy maintenance.
- Quiet design. High-efficiency cross flow blade and imported silence valve are adopted, which greatly reduce the noise of entire unit
- I-feel function. When I-feel function is activated, the unit can detect the temperature around the user and adjust the temperature, so that the comfort of user is improved.
- Multiple protections - anti-freezing protection, temperature sensor malfunction protection, fan motor overload protection.

CONTROL SYSTEM LINEUP



STANDART
Wireless
controller
YAPIF



OPTIONAL
Wired
controller
XK46



Model			AMV6-22WM/ AMV5-22WM2	AMV6-28WM/ AMV5-28WM2	AMV6-36WM/ AMV5-36WM2	AMV6-45WM/ AMV5-45WM2	AMV6-56WM/ AMV5-56WM2	AMV6-71WM/ AMV5-71WM2	AMV6-80WM/ AMV5-80WM2	AMV6-100WM AMV5-100WM2	
Capacity	Cooling	kW	2.2	2.8	3.6	4.5	5.6	7.1	8	9.5	
	Heating	kW	2.5	3.2	4	5	6.3	7.5	9	10.5	
Power Supply		V/Ph/Hz	220-240V ~ 50Hz & 208-230V ~ 60Hz								
Power consumption		W	20	20	25	35	50	65	80	100	
Airflow volume (H/M/L)		m3/h	500/440/300	500/440/300	630/460/320	850/580/500	1100/850/650	1100/850/650	1550/1050/800	1650/1100/900	
Rated current	Cooling	A	0.1	0.1	0.12	0.17	0.24	0.31	0.41	0.41	
	Heating	A	0.1	0.1	0.12	0.17	0.24	0.31	0.41	0.41	
Sound pressure level (H/M/L)		dB(A)	35/33/30	35/33/30	38/35/31	43/40/37	43/41/37	44/41/37	49/46/40	52/48/40	
Connection pipe	Gas pipe	mm	Φ9.52	Φ9.52	Φ12.7	Φ12.7	Φ15.9	Φ15.9	Φ15.9	Φ15.9	
	Liquid pipe	mm	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ9.52	Φ9.52	Φ9.52	Φ9.52	
Drain pipe	External dia.	mm	Φ20	Φ20	Φ20	Φ20	Φ20	Φ20	Φ20	Φ20	
	Thickness	mm	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	
Dimension (WxDxH)	Outline	mm	845×209×289			970×224×300		1078×246×325		1350×258×326	
	Package	mm	976×281×379			1096×308×395		1203×338×425		1496×357×433	
Net weight/Gross weight		kg	10.5/12.5			12.5/15.5		16/19		18.5/23.5	