

AMV6 CASSETTE TYPE UNIT

Compact 4-way Cassette

- Compact design for easy installation. Units maintain the uniform length and width with consistent ceiling opening and panel dimension, convenient for design and installation.
- Ultra-low noise operation. DC inverter motor can realize stepless speed regulation to lower noise. Indoor unit can be set to work under auto quiet mode via wired controller.



Model			AMV6-15CC	AMV6-22CC	AMV6-28CC	AMV6-36CC	AMV6-45CC	AMV6-56CC
Capacity	Cooling	kW	1.5	2.2	2.8	3.6	4.5	5.6
	Heating	kW	1.8	2.5	3.2	4	5	6.3
Power Supply		V/Ph/Hz	220-240V ~ 50Hz & 208-230V ~ 60Hz					
Power consumption		W	30	30	30	30	45	45
Airflow volume (H/M/L)		m3/h	460/420/370	500/460/370	570/480/420	620/550/480	730/650/560	730/650/560
Rated current	Cooling	A	0.15	0.15	0.15	0.15	0.23	0.23
	Heating	A	0.15	0.15	0.15	0.15	0.23	0.23
Sound pressure level (H/M/L)		dB(A)	33/30/25	36/31/25	36/33/28	39/37/35	43/41/39	43/41/39
Connection pipe	Gas pipe	mm	Φ9.52	Φ9.52	Φ9.52	Φ12.7	Φ12.7	Φ15.9
	Liquid pipe	mm	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ9.52
Drain pipe	External dia.	mm	Φ25	Φ25	Φ25	Φ25	Φ25	Φ25
	Thickness	mm	2.5	2.5	2.5	2.5	2.5	2.5
Main body	Dimension (WxDxH)	Outline	570×570×265					
		Package	698×653×295					
	Net weight/Gross weight	kg	17.5/22.5	17.5/22.5	17.5/22.5	17.5/22.5	17.5/22.5	17.5/22.5
Panel	Dimension (WxDxH)	Outline	620×620×47.5					
		Package	701×701×125					
	Net weight/Gross weight	kg	3.0/4.5	3.0/4.5	3.0/4.5	3.0/4.5	3.0/4.5	3.0/4.5

CONTROL SYSTEM LINEUP



STANDART

 Wireless
controller
YAPIF


OPTIONAL

 Wired
controller
XK46

